(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization

International Bureau



(43) International Publication Date 7 October 2004 (07.10.2004)

PCT

(10) International Publication Number WO 2004/085860 A1

(51) International Patent Classification⁷: 21/06, 21/16, B60R 21/16, B64G 1/64

F16B 1/00,

(21) International Application Number:

PCT/AU2004/000371

(22) International Filing Date: 24 March 2004 (24.03.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

2003901352 2003905644 24 March 2003 (24.03.2003) AU 15 October 2003 (15.10.2003) AU

(71) Applicant (for all designated States except US): TELEZYGOLOGY INC. [AU/AU]; Suite 1101, 61 Lavender Street, Milsons Point, NSW 2061 (AU).

(72) Inventors; and

(75) Inventors/Applicants (for US only): RUDDUCK,
Dickory [AU/AU]; 81 Castle Circuit, Seaforth, NSW


2092 (AU). HORT, Michael, John, Laybourne [AU/AU]; 3 Sylvia Street, Chatswood, NSW 2067 (AU). MCARTHUR, Adam, Russell [AU/AU]; 3/63 Lenton Parade, Waterloo, NSW 2017 (AU). NG, Nicholas, Anthony [AU/AU]; South Tower 103, 233 Harris Street, Pyrmont, NSW 2009 (AU). SIZER, Geoffrey, David [AU/AU]; Unit 5, 33 Ryde Road, Pymble, NSW 2073 (AU).

(74) Agents: CHRYSILIOU, Kerry et al.; Chrysiliou Law, Level 2, 15-19 Parraween Street, Cremorne, Sydney, NSW 2090 (AU).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

[Continued on next page]

(54) Title: FASTENER FOR AIR BAGS AND OTHER USES



(57) Abstract: The invention provides a fastener (10) for releasably securing a first element, such as an air bag (12) to a second element such as a bracket (14) located in a vehicle. Fastener (10) has a locking pin (16) which is movable between a locked position and a release position. Locking pin (16) has an engageable head (18). Fastener (10) includes means such as clip (22) for engaging head (18). Locking pin (16) is biased to the release position, for example, by spring (26). Fastener (10) includes an actuator such as spring (32), comprising or including shape memory alloy and adapted to elongate upon application of appropriate energy. When spring (32) is elongated, it causes locking pin (16) to move to the release position. The invention also provides a fastener assembly (130) including at least one post (122) having a groove (124). Fastener assembly (130) includes a bar or latch. for example, in the form of wire (126) adapted to engage the groove (124). Attached to bar (126) is connecting

means, such as shape memory spring (128). Upon application of suitable energy, spring (128) is adapted to change shape and draw bar (126) out of engagement with groove (124).